



1. Versatile usage as **leaning, extension and stepladder**.
2. **Durable stiles** of high quality extruded profile.
3. **Comfortable, wide rungs** with 30 mm rung depth.
4. **Stable cross-beam** for high stability.
5. **High-strength restraining straps**.



	2x6	2x8	2x10	2x12	2x14
Number of rungs					
Stile top/bottom (approx. mm)	60/60	60/60	60/60	71/71	71/71
Number of rungs at max. extension	10	13	16	20	24
Length retracted/extended (approx. m)	1.72/2.84	2.28/3.69	2.84/4.52	3.40/5.64	3.96/6.76
Standing height step ladder/leaning ladder (approx. m)	0.96/1.82	1.50/2.63	2.01/3.44	2.54/4.52	3.06/5.57
Reach height step ladder/leaning ladder (approx. m)	2.96/3.82	3.50/4.63	4.01/5.44	4.54/6.52	5.06/7.57
Vertical height step ladder (approx. m)	1.63	2.17	2.68	3.20	3.73
Width extended top/bottom (approx. mm)	350/628	350/796	350/796	350/940	350/1,054
Base width (approx. m)	1.21	1.55	1.91	2.25	2.66
Weight (approx. kg)	6.2	7.9	10.9	13.1	15.5
Order no.	7004512	7004516	7004520	7004524	7004528