



10
YEAR
GUARANTEE

★ ★ ★
MADE IN
GERMANY

4045 Combination ladder, two-section

- › Versatile for use as **leaning, extension and freestanding ladder**.
- › Inner width of the ladder 300 mm (top section).
- › Rolled profile rungs.
- › Solid steel fittings.
- › Spreader lock provided by high-strength 25 mm wide perlon straps.
- › Ladder feet press-fitted in stile.
- › **Sturdy cross-beam** for high stability.



Number of rungs	2×8	2×10	2×12
Stile top/bottom (approx. mm)	60/60	66/66	71/71
Number of rungs at max. extension	14	17	21
Length retracted (approx. m)	2.32	2.88	3.44
Length extended (approx. m)	4.00	4.84	5.98
Standing height freestanding ladder (approx. m)	1.52	2.05	2.59
Reach height freestanding ladder (approx. m)	3.52	4.05	4.59
Standing height leaning ladder (approx. m)	2.93	3.74	4.82
Reach height leaning ladder (approx. m)	4.93	5.74	6.82
Vertical height freestanding ladder (approx. m)	2.05	2.58	3.12
Width extended top/bottom (approx. mm)	355/750	355/948	355/948
Base width (approx. m)	1.55	1.94	2.19
Weight (approx. kg)	9.5	12.1	14.9
Order no.	404516	404520	404524

For an explanation of standing/reach height see on page 5.

Recommended accessories:



P. 126

Ladder holder set
for gutters



P. 122

Folding universal
ladder step



P. 130

Bucket hook
for rung ladders