

STEP EXTENSION LADDER, TWO-SECTION

- Ergonomic working on 80 mm step depth on the upper section. Front step edges flush with stile.
- Lower weight due to the combination of steps and rungs.
- Increased slip resistance of steps and rungs thanks to a high rib extruded profile.
- Easier extension and retraction of the ladder thanks to steel guide fittings with plastic sliders.

Features:

- Ladder inner width 300 mm (top section).
- Solid steel fittings.
- Press-fitted ladder feet.

EN
131Max.
150 kg10
YEAR
GUARANTEE

Number of rungs/steps	2×8	2×10	2×12	2×14
Stile top/bottom (approx. mm)	83/66	83/66	83/71	83/83
Number of rungs/steps at max. extension	14	17	21	25
Length retracted (approx. m)	2.33	2.89	3.45	4.01
Length extended (approx. m)	4.01	4.85	5.97	7.09
Standing height (approx. m)	2.78	3.56	4.60	5.64
Reach height (approx. m)	4.78	5.56	6.60	7.64
Width extended top/bottom (approx. mm)	355/750	355/948	355/948	355/1,200
Weight (approx. kg)	11.2	13.7	16.7	19.3
Order no.	484616	484620	484624	484628

Recommended accessories:



Set of foot pikes
for straight
cross-beams
Page 90



Ladder holder
set for gutters
Page 96



Curved
cross-beam
Page 93



Set of foot pikes
for curved
cross-beams
Page 91