

# HOOKABLE EXTENSION LADDER

- Non-slip, ribbed, rolled profile rungs.
- Robust guide fittings made of steel.
- Secure attachment of the ladder thanks to preassembled, stable suspension hooks.
- Space-saving storage when retracted.
- The variable angle of inclination allows some height compensation.

## Features:

- **Press-fitted ladder feet.**
- **Ladder inner width 300 mm (top section).**
- **Angle of inclination between 65° and 75°.**
- **Hook size 30 mm.**

Max.  
150 kg



**10**  
YEAR  
GUARANTEE

★ ★ ★  
MADE IN  
GERMANY



|  |               |               |               |
|--|---------------|---------------|---------------|
| <b>Number of rungs</b>                                 | <b>2×7</b>    | <b>2×8</b>    | <b>2×10</b>   |
| <b>Stile</b> top/bottom (approx. mm)                   | 60/60         | 60/60         | 66/66         |
| <b>Number of rungs</b> at max. extension               | 12            | 14            | 17            |
| <b>Length</b> retracted (approx. m)                    | 2.14          | 2.42          | 2.98          |
| <b>Length</b> extended (approx. m)                     | 3.54          | 4.10          | 4.94          |
| <b>Standing height</b> (approx. m)                     | 1.00 – 2.35   | 1.27 – 2.89   | 1.81 – 3.70   |
| <b>Reach height</b> (approx. m)                        | 3.00 – 4.35   | 3.27 – 4.89   | 3.81 – 5.70   |
| <b>Vertical height</b> up to leaning point (approx. m) | 2.04 – 3.38   | 2.31 – 3.92   | 3.12 – 4.73   |
| <b>Width</b> extended top/bottom (approx. mm)          | 355/424       | 355/424       | 355/424       |
| <b>Weight</b> (approx. kg)                             | 7.8           | 8.2           | 10.8          |
| <b>Order no.</b>                                       | <b>494614</b> | <b>494616</b> | <b>494620</b> |

Note: This ladder is not a leaning ladder as stipulated by EN 131-1 and may only be used when hooked in place.

## Recommended accessories:



Suspension set  
Page 95