



**H
Y
M
E
R**

**READY FOR USE IN MINUTES.
MAXIMUM SAFETY.**

**DESIGNED FOR PROFESSIONALS: QUICK TO
ASSEMBLE, FLEXIBLE TO MOVE AND WITH
MAXIMUM SLIP RESISTANCE FOR SAFE WORKING.**

MOBILE STOCKER'S LADDER, SINGLE-SIDED ACCESSIBLE

- Spacious work surface and three-sided guardrail for safe, ergonomic work.
- Non-slip, convenient ascent thanks to the large step.
- Effortless manoeuvring thanks to innovative, swivelling spring-loaded castors. Spring force individually adjustable for different load ranges.
- Magnetic front plate with holes (Ø 8.5 mm) for fastening attachments using hooks or magnets.
- Shipped in pre-assembled modules for quick and easy installation.

Features:

- Step depth 200 mm (aluminium profile steps).
- Platform dimensions 600 x 800 mm.
- Guardrail height 1,050 mm.



EN
131-7

R11

Max.
150 kg

10
YEAR
GUARANTEE

MADE IN
GERMANY



Number of steps incl. platform	3	4	5	6	7	8
Stile (approx. mm)	80	80	80	80	80	80
Standing height (height to platform) (approx. m)	0.73	0.95	1.20	1.45	1.70	1.95
Reach height (approx. m)	2.73	2.95	3.20	3.45	3.70	3.95
Vertical height (approx. m)	1.78	2.00	2.25	2.50	2.75	3.00
Width (approx. mm)	773	831	897	963	1,028	1,094
Distance from front to wall (approx. mm)	87	126	170	215	259	303
Base width (approx. m)	1.27	1.44	1.63	1.82	2.01	2.20
Weight (approx. kg)	36.4	40.1	43.9	48.4	52.4	56.6
Order no.	618803	618804	618805	618806	618807	618808

Note: We advise the use of handrails on both sides from size 5 upwards.

Recommended accessories:



Handrail
Order no. 0055769 for number of steps 4+5
Order no. 0055768 for number of steps 6+7
Order no. 0055751 for number of steps 8



Toeboard set
Order no. 0055807

MOBILE STOCKER'S LADDER, DOUBLE-SIDED ACCESSIBLE

- Spacious work surface and both-sided guardrail for safe, ergonomic work.
- Non-slip, convenient ascent thanks to the large step.
- Effortless manoeuvring thanks to innovative, swivelling spring-loaded castors. Spring force individually adjustable for different load ranges.
- Shipped in pre-assembled modules for quick and easy installation.

Features:

- Step depth 200 mm (aluminium profile steps).
- Platform dimensions 600 x 800 mm.
- Guardrail height 1,050 mm.



EN
131-7



Max.
150 kg

10
YEAR
GUARANTEE



Number of steps incl. platform	2×3	2×4	2×5	2×6	2×7	2×8
Stile (approx. mm)	80	80	80	80	80	80
Standing height (height to platform) (approx. m)	0.73	0.95	1.20	1.45	1.70	1.95
Reach height (approx. m)	2.73	2.95	3.20	3.45	3.70	3.95
Vertical height (approx. m)	1.78	2.00	2.25	2.50	2.75	3.00
Width (approx. mm)	773	831	897	963	1,028	1,094
Base width (approx. m)	1.53	1.79	2.08	2.37	2.66	2.95
Weight (approx. kg)	35.0	40.5	45.2	49.6	59.0	63.0
Order no.	618903	618904	618905	618906	618907	618908

Note: We advise the use of handrails on both sides from size 5 upwards.

Recommended accessories:



Handrail

Order no. 0055769 for number of steps 4+5
Order no. 0055768 for number of steps 6+7
Order no. 0055751 for number of steps 8



Toeboard set

Order no. 0055808

MOBILE STOCKER'S LADDER R13, SINGLE-SIDED ACCESSIBLE

- Work safety in the highest slip resistance class R13. Suitable for use in oily areas.
- Spacious work surface and three-sided guardrail for safe, ergonomic work.
- Non-slip, convenient ascent thanks to the large step.
- Effortless manoeuvring thanks to innovative, swivelling spring-loaded castors. Spring force individually adjustable for different load ranges.
- Magnetic front plate with holes (Ø 8.5 mm) for fastening attachments using hooks or magnets.
- Shipped in pre-assembled modules for quick and easy installation.

Features:

- Step depth 200 mm (aluminium perforated steps).
- Platform dimensions 600 x 800 mm.
- Guardrail height 1,050 mm.



EN
131-7



Max.
150 kg

10
YEAR
GUARANTEE



Number of steps incl. platform	3	4	5	6	7	8
Stile (approx. mm)	80	80	80	80	80	80
Standing height (height to platform) (approx. m)	0.73	0.95	1.20	1.45	1.70	1.95
Reach height (approx. m)	2.73	2.95	3.20	3.45	3.70	3.95
Vertical height (approx. m)	1.78	2.00	2.25	2.50	2.75	3.00
Width (approx. mm)	773	831	897	963	1,028	1,094
Distance from front to wall (approx. mm)	87	126	170	215	259	303
Base width (approx. m)	1.27	1.44	1.63	1.82	2.01	2.20
Weight (approx. kg)	38.1	42.2	46.4	51.3	56.2	61.0
Order no.	638803	638804	638805	638806	638807	638808

Note: We advise the use of handrails on both sides from size 5 upwards.

Recommended accessories:



Handrail

Order no. 0055769 for number of steps 4+5
Order no. 0055768 for number of steps 6+7
Order no. 0055751 for number of steps 8



Toeboard set

Order no. 0055807

MOBILE STOCKER'S LADDER R13, DOUBLE-SIDED ACCESSIBLE

- Work safety in the highest slip resistance class R13. Suitable for use in oily areas.
- Spacious work surface and both-sided guardrail for safe, ergonomic work.
- Non-slip, convenient ascent thanks to the large step.
- Effortless manoeuvring thanks to innovative, swivelling spring-loaded castors. Spring force individually adjustable for different load ranges.
- Shipped in pre-assembled modules for quick and easy installation.

Features:

- Step depth 200 mm (aluminium perforated steps).
- Platform dimensions 600 x 800 mm.
- Guardrail height 1,050 mm.




EN
131-7



Max.
150 kg

10
YEAR
GUARANTEE



Number of steps incl. platform	2×3	2×4	2×5	2×6	2×7	2×8
Stile (approx. mm)	80	80	80	80	80	80
Standing height (height to platform) (approx. m)	0.73	0.95	1.20	1.45	1.70	1.95
Reach height (approx. m)	2.73	2.95	3.20	3.45	3.70	3.95
Vertical height (approx. m)	1.78	2.00	2.25	2.50	2.75	3.00
Width (approx. mm)	773	831	897	963	1,028	1,094
Base width (approx. m)	1.53	1.79	2.08	2.37	2.66	2.95
Weight (approx. kg)	37.4	43.6	50.4	58.0	65.7	73.5
Order no.	638903	638904	638905	638906	638907	638908

Note: We advise the use of handrails on both sides from size 5 upwards.

Recommended accessories:



Handrail

Order no. 0055769 for number of steps 4+5
Order no. 0055768 for number of steps 6+7
Order no. 0055751 for number of steps 8



Toeboard set

Order no. 0055808

MOBILE STOCKER'S LADDER, SINGLE-SIDED ACCESSIBLE

- Spacious work surface and three-sided guardrail for safe, ergonomic work.
- Non-slip, convenient ascent thanks to the large step.

Features:

- Step depth 200 mm (aluminium profile steps).
- Platform dimensions 600 x 800 mm.
- Guardrail height 1,003 mm.

EN
131-7



Max.
150 kg

10
YEAR
GUARANTEE



Number of steps incl. platform	3	4	5	6	7	8
Stile (approx. mm)	73	73	73	73	73	73
Standing height (height to platform) (approx. m)	0.73	0.97	1.21	1.46	1.70	1.94
Reach height (approx. m)	2.73	2.97	3.21	3.46	3.70	3.94
Vertical height (approx. m)	1.76	2.00	2.24	2.49	2.73	2.97
Width (approx. mm)	890	890	890	1,070	1,200	1,200
Distance from front to wall (approx. mm)	106	149	192	235	278	321
Base width (approx. m)	1.27	1.45	1.63	1.82	2.00	2.18
Weight (approx. kg)	30.2	34.1	37.7	41.8	45.8	48.8
Order no.	688803	688804	688805	688806	688807	688808

Note: We advise the use of handrails on both sides from size 5 upwards.

Recommended accessories:



Handrail

Order no. 0051777 for number of steps 4+5
Order no. 0051778 for number of steps 6+7
Order no. 0051780 for number of steps 8



Back protection door, self-closing

Order no. 0054880

MOBILE STOCKER'S LADDER, DOUBLE-SIDED ACCESSIBLE

- Spacious work surface and both-sided guardrail for safe, ergonomic work.
- Non-slip, convenient ascent thanks to the large step.

Features:

- Step depth 200 mm (aluminium profile steps).
- Platform dimensions 600 x 800 mm.
- Guardrail height 1,003 mm.

EN
131-7



Max.
150 kg

10
YEAR
GUARANTEE



Number of steps incl. platform	2x3	2x4	2x5	2x6	2x7	2x8
Stile (approx. mm)	73	73	73	73	73	73
Standing height (height to platform) (approx. m)	0.73	0.97	1.21	1.46	1.70	1.94
Reach height (approx. m)	2.73	2.97	3.21	3.46	3.70	3.94
Vertical height (approx. m)	1.76	2.00	2.24	2.49	2.73	2.97
Width (approx. mm)	890	890	890	1,070	1,200	1,200
Base width (approx. m)	1.51	1.79	2.07	2.35	2.63	2.91
Weight (approx. kg)	32.9	37.9	42.9	49.5	54.9	59.7
Order no.	688903	688904	688905	688906	688907	688908

Note: We advise the use of handrails on both sides from size 5 upwards.

Recommended accessories:



Handrail

Order no. 0051777 for number of steps 4+5
Order no. 0051778 for number of steps 6+7
Order no. 0051780 for number of steps 8



Back protection door, self-closing

Order no. 0054880

Hymer-Leichtmetallbau GmbH & Co. KG

Käferhofen 10 | 88239 Wangen | Germany

Telephone +49 75 22 700-700

international-sales@hymer-alu.de | hymer-access.com

hymer-access.com

You can also download all
brochures from our website:



Written information on the products and images thereof may differ from the actual design in individual cases.
Errors, price changes and design modifications are also reserved.

Version: 08/2025